

FASTRACC™

High Speed Trinity Attenuating Crash Cushion



FASTRACC™ TRinity Attenuating Crash Cushion

NCHRP Report 350, Test Level 3

FASTRACC Exceeds TL3
Requirements in Head-on Impacts
up to 112 km/hr (70 mph)

For Permanent or Temporary
(Work Zone) Applications

Modular Design Simply Bolts to
Standard TRACC as an upgrade.

The FASTRACC™ Offers Specifiers, Installers and Users All These Advantages:

- Easy to Install and Inspect.
- Compact Size; 26'-0 (7.9m) Length x 2'-7 (0.8m) Width.
- Unit Ships Complete; No Field Assembly.
- FASTRACC™ Module Can Bolt to Standard TRACC™ System.
- Installs on new or existing Concrete or Asphalt Pad.
- Easily moveable for work zone use.
- Open Design; Familiar Galvanized Steel Components.
- Only Visual Annual Maintenance Required.
- Easily repaired in the field or at the yard.
- Personal Training Seminars by Our Highway Safety Experts are available to Installers and User Groups.



Trinity Industries, Inc.

(800) 644-7976
Fax: (214) 589-8423
Email: tracc.info@trin.net
Website: www.highwayguardrail.com

© 2002 Trinity Industries, Inc.